# Experimental Investigation on Modification of Inlet poppet valve of single cylinder Direct Ignition Four stroke Diesel Engine

Dr. Hiregoudar Yerrennagoudaru<sup>1</sup>, Shiva prasad Desai<sup>2</sup>, Mallikarjuna. A<sup>3</sup>

<sup>1</sup>Professor and PG Co-coordinator (Thermal Power Engineering), Mechanical Engineering Department, RYMEC Bellary, Karnataka, India

<sup>2</sup>M.Tech (Thermal Power Engineering), Research Scholar, Mechanical Engineering Department, RYMEC Bellary, Karnataka, India

<sup>3</sup>M.Tech Student(Thermal Power Engineering), Mechanical Engineering Department, RYMEC Bellary, Karnataka, India

**Abstract:** To generate air swirl inside a direct ignition diesel engine combustion chamber an attempt is made to modify some possible changes in an inlet valves without disturbing the properties of valve material, which ensures an improved combustion and a noticeable improvements in emission levels at its exhaust gases. In order to select better and most suitable modifications in practicality the simulation through CFD is the most precisive and accurate way of selecting the optimum modification in inlet poppet valves. **Keywords:** Swirl, Turbulence, CFD analysis, thermal efficiency HC and CO

### I. Introduction

CI Engines are very useful for high load carrying capacity and torque transmission engines in the world. The power output to weight ratio is more compared to SI engines, but thermal efficiency is less compared to SI engines and is around 22% to 34%. So in order to utilize CI engines one should aim to increase its thermal efficiency as much as possible by some modifications in the engine design. Though the combustion in CI engine is heterogeneous , still we can optimize its combustion efficiency by ensuring heat utilization and marginal reduction in emission levels.

Here three varieties of inlet valves are used,

1. Base model (The conventional inlet poppet valves)

2. Model-1 valve (Inlet valve with 5 straight grooves on its poppet head)

3. Model-2 valve (Inlet valve with 3 masks and 3 straight grooves on its poppet head)

4. Model-3 valve (Inlet valve with 5 straight grooves with 3 fins on its poppet head)

### **II.** Base model (conventional inlet poppet valves):

The conventional inlet valve is as shown above, consisting of combustion face which is exposed to a very high temperatures during the process of combustion. Valve is having a delicate part called seating which should be very accurate enough in dimensions and finishing so that accurate locking and sealing enhances the whole engine performances



Model-1 valve (Inlet valve with 5 straight grooves on its poppet head)



Width of groove: 3mm Depth of groove: 3mm Outer dia of grooves: 22mm Inner dia of grooves: 8mm

Fig-2

Grooving is the process of removing a small piece of metal on the valve head without disturbing the valve seating; the small cavities are called grooves. Here for analysis we have used 2-grooved valves, 3- grooved valve and 5- grooved valve, which are having the following dimensions:

Model-2 valve (Inlet valve with 3 masks and 3 straight grooves on its back)



Width of groove: 3mm Depth of groove: 3mm Outer dia of grooves: 22mm Inner dia of grooves: 8mm Angle of each mask: 45degrees. Thickness of mask: 4mm Width of mask: 4mm

Fig-3

In this type a valve consisting a grooves three in numbers with small pieces build on head as shown in fig-2. This type of design utilizes a combination of small built-up pieces called MASKS and a CAVITIES called grooves. For analysis 2groove-2mask, 3Groove-3masks are simulated through CFD.

Model-3 valve (Inlet valve with 5 straight grooves with 3 fins on its poppet head)



Width of groove: 3mm Depth of groove: 3mm Outer dia of grooves: 22mm Inner dia of grooves: 8mm Dia of ring: 7.9mm Length of blade: 6.5mm Width: 4mm

Fig-4

In this type a small ring with blades are attached to valve as shown in figure-3. It uses a combination of grooves three in numbers and a freely rotatable ring with 3 blades. For CFD analysis the 3Groove-5bladed ring and 5groove-3bladed ring are simulated.

#### Simulation using CFD:

Simulation requires valve models, engine inlet manifold model, combustion chamber model, engine operating parameters. Discussion of each may become a very lengthy topics hence just explained through some neat sketches.

Engine operating parameters:								
WATER COOLED, SINGLE CYLINDER, 4-STROKE DIESEL ENGINE SPECIFICATIONS:								
BHP = 5HP	= 3.68KW							
Bore Diameter	= 80mm							
Stroke length	= 110mm							
Speed	= 1500rpm							
Brake drum Radius	= 147mm							
C.V of Diesel	= 45, 355 Kj / Kg							
Specific Gravity of diesel	= 0.8225gms/cc							
Orifice dia	= 15mm							
Brake Rope dia	= 15.9 mm							
Torque arm radius	= 0.2  mts							
Compression ratio	= 16.5:1							

#### Simulation By Using Cfd:

Here valve lift is considered as major criterion for simulation.

Total valve lift = 12mm

This 12mm is divided into 3 parts and called as

Low Lift (valve at 4mm downward movement)

Medium lift (valve at 8mm downward movement)

High lift (valve at12mm downward movement)

Hence CFD simulations were carried out for analyzing swirl, turbulence, velocity of inlet air and also pressure distribution inside the cylinder during suction stroke and are analyzed at different inlet valve lift positions in comparison with base model.

#### III. **ANALYSIS OF SWIRL BY SIMULATION:** VELOCITY, VECTOR, PRESSURE, TURBULENT KINETIC ENERGY PLOTS AT MAXIMUM VALVE LIFT (12 MM)

91.77

81.57

71.38

61.18

50.98 40.79

30.59

20.39

10.20

0.00

#### **1 BASE MODEL:**



Velocity magnitude in cylinder and manifold



Velocity vector plot 1mm below the valve



Turbulent kinetic energy plot of entire assembly

Velocity (m/s) 59.02

52.48

45.93

39.39

32.85

26.31

19.76

13.22

6.68

0.14

### 2. Five Straight Grooves Model





Velocity magnitude in cylinder and manifold



Velocity vector plot 1mm below the valve



Pressure plot in cylinder and manifold

### 3. Three Straight Grooves and Three Mask

Turbulent kinetic energy plot of entire assembly



Velocity magnitude in cylinder and manifold





Pressure plot in cylinder and manifold

Turbulent kinetic energy plot of entire assembly



### 4. Five Straight Grooves Three Fins Model:

Velocity magnitude in cylinder and manifold

Velocity vector plot 1mm below the valve



Pressure plot in cylinder and manifold

Turbulent kinetic energy plot of entire assembly

52.86

47.00

41.14

35.27

29.41 23.54

17.68

11.81

5.95

0.08

Hence a table of swirl ratios and turbulent kinetic energy can Give ideas to optimize the swirl through inlet valves: the tables are as follows

			Valve movement (full 24mm)								
		Valve lift in (mm) Forward			В						
		4.00	8.00	12.00	16.00	20.00	24.00				
	Swirl Ratio	2.08	1.76	1.50	1.37	1.36	0.95				
Base Model	Tumble Ratio	15.21	15.64	15.69	17.29	30.15	1.63				
	TKE(j/kg)	8.85	57.14	95.05	111.55	61.81	5.49				
	Mass Flow Rate(kg/s)			0.0290							

### TABLE-1

			V	alve movemer	nt (full 24mm)		
		Valve li	ift in (mm) F	orward	B	ackward	
		4.00	8.00	12.00	16.00	20.00	24.00
Five Straight	Swirl Ratio	1.72	1.62	1.45	1.49	1.36	0.83
	Tumble Ratio	14.64	15.96	16.57	17.50	30.21	1.68
	TKE(j/kg)	8.68	53.25	90.09	107.13	54.92	11.87
	Mass Flow Rate(kg/s)			0.02	279		

#### TABLE-2

			Valve movement (full 24mm)							
		Valve l	ift in (mm) F	orward	В	ackward				
		4.00	8.00	12.00	16.00	20.00	24.00			
	Swirl Ratio	1.82	1.62	1.42	1.46	1.36	0.87			
Five Curved	Tumble Ratio	15.74	15.76	16.07	17.70	30.74	1.63			
	TKE(j/kg)	8.61	55.87	<b>91.78</b>	109.72	54.02	5.77			
	Mass Flow Rate(kg/s)			0.02	286					

#### TABLE-3

		Valve movement (full 24mm)						
		Valve lift in (mm) Forward Backward						
		4.0000	8.0000	12.0000	16	20	24	
	Swirl Ratio	1.55	1.25	1.09	1.08	0.97	0.70	
2Grooves2Mask	Tumble ratio	15.12	16.32	15.71	16.69	30.07	1.54	
	TKE(j/kg)	8.65	38.26	85.45	99.08	33.92	3.84	
	Mass Flow Rate(kg/s)	0.0266						

## TABLE-4

		Valve movement (full 24mm)						
		Valve lift in (mm) Forward Backward						
		4.0000	8.0000	12.0000	16	20	24	
3Grooves3Mask	Swirl Ratio	1.43	1.38	1.29	1.35	1.11	0.87	
	Tumble ratio	15.28	16.09	16.29	17.59	14.23	0.49	
	TKE(j/kg)	8.26	23.55	71.18	82.40	56.32	1.48	
	Mass Flow Rate(kg/s)			0.02351				

TABLE-5

		Valve movement (full 24mm)							
		Valve lift in (mm) Forward Backward							
		4.0000	8.0000	12.0000	16	20	24		
	Swirl Ratio	2.28	2.39	2.06	1.98	1.84	1.22		
3Grooves3Fin	Tumble Ratio	<b>14.86</b>	17.59	14.90	15.73	16.32	1.98		
	TKE(j/kg)	9.01	51.85	86.72	100.84	59.66	10.48		
	Mass Flow Rate(kg/s)			0.0276	3				

*Volume – 01, Issue – 03, June – 2016, PP – 43-53* 

TABLE-6

		Valve movement (full 24mm)							
		Valve lift in (mm) Forward Backward							
		4.0000	8.0000	12.0000	16	20	24		
5Grooves3Fin	Swirl Ratio	1.86	1.62	1.60	1.52	1.33	0.83		
	Thumble Ratio	14.63	14.89	14.68	16.71	28.45	1.24		
	TKE(j/kg)	9.25	50.39	88.58	97.18	54.07	7.07		
	Mass Flow Rate(kg/s)	0.02729							

Here by observation of swirl and turbulent kinetic energy in above tables and graphs one can choose the best type of valve which will give optimum results among all varieties.

Hence we can go for 5GROOVED TYPE, 3GROOVED-3MASKED TYPE AND 5GROOVED-3FINNED TYPE INLET VALVES for physical models.

#### Physical model preparation:

- 1. Same valve material is selected for making fins and masks on the inlet valves because of;
- 2. It can with stand high temperature up to  $800^{\circ}$ C to  $1000^{\circ}$ C.
- 3. It is wear resistant.
- 4. Grooving is done by CNC machines.
- 5. Masks are welded by TIG welding set up.

### Type-1 valve (physical model):



Fig-5 (Valve With 5 Grooves)

Type-2 valve :



FIG-6 (Valve with 3 grooves and 3 masks)



FIG-7 VALVE WITH 5GROOVES & 3 FIN

IV.Experimental Set Up (Test Rig):Kirloskar Make Four Stroke Single Cylinder Diesel Engines Of Av Series.



FIG-8 TEST SET UP



V. Experimental Analysis:

### TABLE-8

TYPE OF VALVE MODEL	BRAKE THERMAL EFFICIENCY %	INDICATED THERMAL EFFICIENCY %	MECHANICAL EFFICIENCY %	SFC kg/KWH	CO %	НС РРМ
BASE MODEL	6 TO 32	32 TO 45	18 TO 71	1.3 TO 0.519	0.11 TO 0.06	130 TO 80
5 STRAIGHT GROOVES	6.15 TO 36.9	32.13 TO 54.22	19.15 TO 73.14	1.28 TO 0.21	0.14 TO 0.01	110 TO 10
3 GROOVES 3 MASKS	6.15 TO 32.11	32.13 TO 48.05	19.15 TO 73.14	1.28 TO 0.24	0.11 TO 0.05	160 TO 30
5 STRAIGHT GROOVES WITH 3 FIN	8.74 TO 35.5	33.34 TO 52.1	26.2 TO 74	0.907 TO 0.22	0.178 TO 0.035	115 TO 25



*Volume – 01, Issue – 03, June – 2016, PP – 43-53* 





Volume – 01, Issue – 03, June – 2016, PP – 43-53

MECHANICAL EFFICIENCY (%)







### Conclusions

- VI. Optimization of inlet air to the engine can be done by means of inlet poppet valves. 1.
- 2. CFD simulation can advise better results.
- 3. Masking of inlet valves improves swirl rate and intern brake thermal efficiency of engine.
- 4. Fins also increase the swirl rate and hence we can get better thermal efficiency.
- 5. Pollution levels are also decreased with all varieties of valves when compared to conventional valve.
- Manufacturing cost of masks and grooves are less and can easily prepared 6.

#### VII. **Future Recommendations**

- 1. The shape of masks and grooves can be changed and to be checked.
- 2. The design and shape of fins blades can also be thoroughly studied.
- 3. The inlet valve rotation during process can be made static to enhance good swirl rates.
- The engine valves can be modified to generate air swirl at the entrance for better performances. 4.
- 5. Engine size can be made compact for same capacities with use of less air, i.e., with lower volumetric efficiencies and at high swirl rates for the same capacity, the engine can be made compact in size

#### References

- Ariz Ahmad : Analysis of Combustion Chambers in Internal Combustion Engine [1].
- H. Belmabrouk and M. Michard : Amalysis of the swirl effect on turbulent length scales in an ICE [2]. cylinder by two-point LDV
- Vinodh Kumar B, Sivagaminathan N, Gopalakrishnan N, Scott Morton and Paul Radavich :AIR [3]. FLOW AND CHARGE MOTION STUDY OF ENGINE INTAKE PORT
- [4]. A. C. Hansen : Modelling gas flow in a direct injection diesel engine: I - Squish and swirl
- Rajinder Kumar Soni and Pranat Pal Dubey :DIESEL ENGINE AIR SWIRL MESUREMENTS [5]. USING AVL TEST RIG