Modeling and Analysis of Composite Propeller Shaft

Dr.R.GANAPATHI¹, Dr.B.OMPRAKASH², J.VINAY KUMAR³

¹Professor, Dept of Mechanical Engineering, Anurag engineering college, Telangana, India, ²Assistant Professor, Dept of Mechanical Engineering, JNTUA, AP, India, ³PG Student, Dept of Mechanical Engineering (AICE), JNTUA, AP, India.

Abstract: This paper deals with modeling and analysis of composite drive shaft by replacing the conventional stainless steel with composite materials. Conventional drive shaft is a two piece steel drive shaft in order to make it as a single long continuous shaft we are using composite materials. Static, model and buckling analysis on these materials is done by using ANSYS software. The materials which use in this analysis were E-glass epoxy, high strength carbon epoxy, and high modulus carbon epoxy.

Introduction

Drive shaft is a mechanical instrument which is used in automobiles. Most popularly this drive shaft is known as the propeller shaft, while coming to the construction it was long cylindrical structure consists of thee universal joints. Drive shaft is used to transfer the rotary motion to the differential by using the helical gear box. This rotary motion is used to run the rear wheels. In many cases we use stainless steel shaft for the fabrication of drive shaft. This drive shaft has wide applications in automobile world, used in the vehicles like trucks, buses, aero planes etc.

Problem Description

Stainless steel was mainly used because of its high strength. But this stainless steel shaft has less specific strength and less specific modulus. Stainless steel has less damping capacity. Because of its higher density of molecules of stainless steel, its weight is very high. Because of increase in weight fuel consumption will in increase, the effect of inertia will be more.

Because of increase in weight of the propeller shaft we are replacing the stainless steel with the composite materials, which are very less weight when compared to that of stainless steel. The cost of composite materials is less when compared to that of stainless steel.

Composite Materials and Its Classification

Composite materials are used in the fabrication of drive shaft in place of stainless steel. Composite materials have high specific strength and high specific modulus. Thermal conductivity properties are different for these composite materials. Because of using various composite materials in layer by layer the Conductivity properties vary for each material, because of this reason there was drastic increase in thermal conductivity. The molecular density is less when compared to that of stainless steel the weight will be decreased. Mainly we use E-glass epoxy HS carbon epoxy Kevlar glass fiber materials are used in manufacturing.

Composite materials are classified according to their properties

- Polymer matrix composites
- Metal matrix composites
- Ceramic matrix composites

These composite materials are classified based on the matrices composite material composites. Polymer matrices are not stronger than metal matrix; these composites are made in composite resin.

Applications of Composite Materials

Automotives: Glass/epoxy leaf springs for heavy trucks, clutch plates, drive shafts, frames, engine blocks etc.

Space: Remote Manipulator Arm, High Gain Antenna, Antenna Ribs, Struts Etc.

Aircrafts: Driveshaft, rudders, elev-ators' etc.

Types of Drive Shaft

There are various type of transmission shaft among them following are important

1. Transmission shaft.

Volume – 02, *Issue* – 11, *November* – 2017, *PP* – 24-28

- 2. Machine shaft.
- 3. Spindle.
- 4. Automobile drive shaft.
- 5. Ship propeller shaft.
- 6. Helicopter tail rotor shaft.

These drive shafts can be manufactured by replacing the stainless steel with the composite materials.

Comparision of Stainless Steel with Composite Materials

| icss succi with C | omposite Materi |
|-------------------|--|
| STAINLESS | COMPOSITE |
| STEEL | MATERIALS |
| LOW | HIGH |
| | |
| LOW | HIGH |
| | |
| HIGH | LOW |
| HIGH | LOW |
| HIGH | LOW |
| MEDIUM | MEDIUM |
| | |
| MEDIUM | HIGH |
| | |
| | STAINLESS STEEL LOW LOW HIGH HIGH HIGH MEDIUM |

Improvements Made To the Drive Shaft

- ➤ Long continuous drive shaft is made by replacing the discontinuous two piece conventional drive shaft.
- Reducing the weight of the drive shaft.
- > Increase in natural frequency.
- Decrease in bending stress using various stacking sequence.
- ➤ Increase in torque transmission and torsion buckling activities

Comparision of Mechanical Properties

| STAINLESS | HSCARBON/E- |
|-----------|---------------------------|
| STEEL | GLASS EPOXY |
| 207Gpa | 210Gpa |
| | |
| 80Gpa | 70Gpa |
| | |
| 370Mpa | 420Mpa |
| | |
| 7600Kg/m3 | 1600Kg/m3 |
| | 207Gpa 80Gpa 370Mpa |

Analysis of Composite Drive Shaft Using Ansys

ANSYS is an analysis tool which was used by mechanical engineers to check the feasibility of any product before launching into the market. Various analysis can be done before launching the product into the market. Various types of analysis techniques were used among them static, model, buckling, CFD etc.

In this scenario we consider buckling, model, and static analysis by finite element technique. From these analysis techniques we got the following results.

Finite Element Analysis

Finite element analysis is a computer based numerical technique is used to for calculating the strength and behavior of the engineering structures. The structure on which the analysis can be done is divided into large number of finite elements and required stress at the desired point can be calculated. The accuracy of the structure depends on the no of finite elements made.

Volume – 02, *Issue* – 11, *November* – 2017, *PP* – 24-28

Static Analysis

Static analysis deals with the conditions of equilibrium of the bodies acted upon by the forces. Types of static analysis


- Linear
- Non linear

Model Analysis


The body under the equilibrium was disturbed from its state by the action of some external inherent force then the system undergoes vibrations these vibrations are called free vibrations. It will vibrate with its natural frequency and its amplitude. Model analysis is used to determine the natural frequencies and mode shape of the structures

Analysis on E-Glass Epoxy


E-glass epoxy has the following results in von-mice's and in all DOF




ALL DOF ANALYSIS FOR E-GLASS EPOXY



VON-MICES ANALYSIS OF E-GLASS EPOXY




MODEL ANALYSIS FOR E-GLASS EPOXY




BUCKLING ANALYSIS OF E-GLASS EPOXY


HS-CARBON EPOXY HAS THE FOLLOWING RESULTS IN ANSYS




ALL DOF ANALYSIS FOR HS-CARBON EPOXY




VON-MICES ANALYSIS FOR THE HS-CARBON EPOXY



ALL DOF FOR HM CARBON EPOXY



VON MICES ANALYSIS FOR HM-CARBON EPOXY



MODEL ANALYSIS FOR HM CARBON EPOXY

Conclusion

Hence by using composite materials weight of the drive shaft was successfully decreased. Finite element analysis was used in this work to predict the deformation of the shaft. Bernoulli–Euler and Timoshenko beam theories was used to know the natural frequency. Hence single piece high strength carbon/epoxy composite drive shaft has been proposed to design to replace two piece conventional steel drive shaft of automobile.

References

- [1]. John W.et.al.engineers Guide to composite materials, American society for metals, 1986.
- [2]. Beardmore, P.et al. the potential for composites in structural Automotive Aplications J. of composites science and Technology 26 1986: pp. 251-281.
- [3]. T. RANGASWAMY, et al. "Optimal sizing and stacking sequence of composite drive shaft" ISSN1392-1320 materials science (medziagotyra). Vol. 11, no.2, 2005.
- [4]. 4.Rajeev S and Krishnamurthy, C.S,1992 "Discrete optimization of structure using genetic Algorithm" Journal of struct. Engg .ASCE Vol. 118PP. 1233-1250
- [5]. Pollard, A. polymer Matrix composites in drive line applications, GNK Tech., uk, 1989.
- [6]. Goldberg, D. E. Genetic Algorithms in Search, Optimization and Machine Learning, Reading MA, Addison-Wesley.
- [7]. Vijayarangan, S., Rajendran, I. Optimal Design of a Composite Leaf Spring Using Genetic Algorithm Computers and Structures 79 2001: pp. 1121 1129.
- [8]. T.Rangaswamy, et. al "Optimal Design and Analysis of Automotive Composite Drive Shaft", International Symposium of Research Students on Materials Science and Engineering December 2002-04 Chennai India
- [9]. Kim C D et. al. 1992, "Critical speed Analysis of Laminated Drive Shafts", Composite Engg. Vol.3, pp. 633-643.
- [10]. J. H. Park, J. H. Wang 2001, "Stacking sequence Design of Composite Laminates for maximum Strength Using Genetic Algorithm", Journal of Composite Structures, Vol.52, pp. 217-231.